

Polarized (DC Type)



Catalog #	Max. DC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series A 1" x 1"					
SD1543-4	90	240	67	1.0625	8-32
SD1543-5	112	300	67	1.1875	8-32
SD1543-6	135	360	67	1.3125	8-32
SD1543-7	157	420	67	1.3750	8-32
SD1543-8	180	480	67	1.5000	8-32
SD1543-9	202	540	67	1.5625	8-32
SD1543-10	225	600	67	1.6875	8-32
SD1543-11	247	660	67	1.8125	8-32
SD1543-12	270	720	67	1.8750	8-32
SD1543-13	292	780	67	2.0000	8-32
SD1543-14	315	840	67	2.0625	8-32
SD1543-15	337	900	67	2.1875	8-32
SD1543-16	360	960	67	2.3125	8-32
SD1551-17	382	1020	68	2.6250	8-32
SD1551-18	405	1080	68	2.7500	8-32
SD1551-19	427	1140	68	2.8750	8-32
SD1551-20	450	1200	68	2.9375	8-32
SD1551-21	472	1260	68	3.0625	8-32
SD1551-22	495	1320	68	3.1875	8-32
SD1551-23	517	1380	68	3.3125	8-32
SD1551-24	540	1440	68	3.3750	8-32
SD1551-25	562	1500	68	3.5000	8-32
SD1551-26	585	1560	68	3.5625	8-32
SD1551-27	607	1620	68	3.6875	8-32
SD1551-28	630	1680	68	3.8125	8-32
SD1551-29	652	1720	68	3.8750	8-32
SD1551-30	675	1800	68	4.0000	8-32

Peak discharge current - amperes 3

Catalog #	Max. DC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series C 1 1/2" x 1 1/2"					
SD3066-4	90	240	67	1.0625	8-32
SD3066-5	112	300	67	1.1875	8-32
SD3066-6	135	360	67	1.3125	8-32
SD3066-7	157	420	67	1.3750	8-32
SD3066-8	180	480	67	1.5000	8-32
SD3066-9	202	540	67	1.5625	8-32
SD3066-10	225	600	67	1.6875	8-32
SD3066-11	247	660	67	1.8125	8-32
SD3066-12	270	720	67	1.8750	8-32
SD3066-13	292	780	67	2.0000	8-32
SD3066-14	315	840	67	2.0625	8-32
SD3066-15	337	900	67	2.1875	8-32
SD3066-16	360	960	67	2.3125	8-32
SD3066-17	382	1020	68	2.6250	8-32
SD3066-18	405	1080	68	2.7500	8-32
SD3066-19	427	1140	68	2.8750	8-32
SD3066-20	450	1200	68	2.9375	8-32
SD3066-21	472	1260	68	3.0625	8-32
SD3066-22	495	1320	68	3.1875	8-32
SD3066-23	517	1380	68	3.3125	8-32
SD3066-24	540	1440	68	3.3750	8-32
SD3066-25	562	1500	68	3.5000	8-32
SD3066-26	585	1560	68	3.5625	8-32
SD3066-27	607	1620	68	3.6875	8-32
SD3066-28	630	1680	68	3.8125	8-32
SD3066-29	652	1720	68	3.8750	8-32
SD3066-30	675	1800	68	4.0000	8-32

Peak discharge current - amperes 9

Catalog #	Max. DC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series E 2" x 2"					
SD2619-4	90	240	67	1.8750	1/4-20
SD2619-5	112	300	67	2.1250	1/4-20
SD2619-6	135	360	67	2.3750	1/4-20
SD2619-7	157	420	67	2.6250	1/4-20
SD2619-8	180	480	67	2.8750	1/4-20
SD2107-9	202	540	68	3.0000	1/4-20
SD2107-10	225	600	68	3.2500	1/4-20
SD2107-11	247	660	68	3.5000	1/4-20
SD2107-12	270	720	68	3.6875	1/4-20
SD2107-13	292	780	68	3.8750	1/4-20

POLARIZED CONTINUED ON NEXT PAGE

Non-Polarized (AC Type)



Catalog #	Max. AC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series A 1" x 1"					
SD1544-1	26	63	67	0.9375	8-32
SD1544-2	52	126	67	1.1250	8-32
SD1544-3	78	189	67	1.3125	8-32
SD1544-4	104	252	67	1.5000	8-32
SD1544-5	130	315	67	1.6875	8-32
SD1544-6	156	378	67	1.9375	8-32
SD1544-7	182	441	67	2.1250	8-32
SD1544-8	208	504	67	2.3125	8-32
SD1544-9	234	567	68	2.7500	8-32
SD1544-10	260	630	68	3.0000	8-32
SD1544-11	286	693	68	3.1875	8-32
SD1544-12	312	756	68	3.3750	8-32
SD1544-13	338	819	68	3.5625	8-32
SD1544-14	364	882	68	3.7500	8-32
SD1544-15	390	945	68	4.0000	8-32
SD1544-16	416	1008	68	4.1875	8-32
SD1544-17	442	1071	68	4.3750	8-32
SD1544-18	468	1134	68	4.5625	8-32
SD1544-19	494	1197	68	4.7500	8-32
SD1544-20	520	1260	68	5.0000	8-32

Peak discharge current - amperes 3

Catalog #	Max. AC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series C 1 1/2" x 1 1/2"					
SD3067-1	26	63	67	0.9375	8-32
SD3067-2	52	126	67	1.1250	8-32
SD3067-3	78	189	67	1.3125	8-32
SD3067-4	104	252	67	1.5000	8-32
SD3067-5	130	315	67	1.6875	8-32
SD3067-6	156	378	67	1.9375	8-32
SD3067-7	182	441	67	2.1250	8-32
SD3067-8	208	504	67	2.3125	8-32
SD3067-9	234	567	68	2.7500	8-32
SD3067-10	260	630	68	3.0000	8-32
SD3067-11	286	693	68	3.1875	8-32
SD3067-12	312	756	68	3.3750	8-32
SD3067-13	338	819	68	3.5625	8-32
SD3067-14	364	882	68	3.7500	8-32
SD3067-15	390	945	68	4.0000	8-32
SD3067-16	416	1008	68	4.1875	8-32
SD3067-17	442	1071	68	4.3750	8-32
SD3067-18	468	1134	68	4.5625	8-32
SD3067-19	494	1197	68	4.7500	8-32
SD3067-20	520	1260	68	5.0000	8-32

Peak discharge current - amperes 9

Catalog #	Max. AC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series E 2" x 2"					
SD2650-1	26	63	67	1.3750	1/4-20
SD2650-2	52	126	67	1.8750	1/4-20
SD2650-3	78	189	67	2.2500	1/4-20
SD2650-4	104	252	67	2.7500	1/4-20
SD2650-5	130	315	68	3.1250	1/4-20
SD2650-6	156	378	68	3.6250	1/4-20
SD2650-7	182	441	68	4.0000	1/4-20
SD2650-8	208	504	68	4.5000	1/4-20
SD2650-9	234	567	68	5.0000	1/4-20
SD2650-10	260	630	68	5.3750	1/4-20
SD2650-11	286	693	68	5.8750	1/4-20
SD2650-12	312	756	68	6.3750	1/4-20
SD2650-13	338	819	68	6.7500	1/4-20
SD2650-14	364	882	68	7.2500	1/4-20
SD2650-15	390	945	68	7.6250	1/4-20
SD2650-16	416	1008	68	8.1250	1/4-20
SD2650-17	442	1071	68	8.6250	1/4-20
SD2650-18	468	1134	68	9.0000	1/4-20
SD2650-19	494	1197	68	9.5000	1/4-20
SD2650-20	520	1260	68	9.8750	1/4-20

Peak discharge current - amperes 15

NON-POLARIZED CONTINUED ON NEXT PAGE

Polarized (DC Type)



Catalog #	Max. DC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series E 2" x 2" Continued					
SD2107-14	315	840	68	4.1250	1/4-20
SD2107-15	337	900	68	4.3750	1/4-20
SD2107-16	360	960	68	4.5625	1/4-20
SD2107-17	382	1020	68	4.8125	1/4-20
SD2107-18	405	1080	68	5.0000	1/4-20
SD2107-19	427	1140	68	5.2500	1/4-20
SD2107-20	450	1200	68	5.5625	1/4-20
SD2107-21	472	1260	68	5.7500	1/4-20
SD2107-22	495	1320	68	6.0000	1/4-20
SD2107-23	517	1380	68	6.1875	1/4-20
SD2107-24	540	1440	68	6.3750	1/4-20
SD2107-25	562	1500	68	6.6250	1/4-20
SD2107-26	585	1560	68	6.8750	1/4-20
SD2107-27	607	1620	68	7.0625	1/4-20
SD2107-28	630	1680	68	7.2500	1/4-20
SD2107-29	652	1720	68	7.5000	1/4-20
SD2107-30	675	1800	68	7.7500	1/4-20

Peak discharge current - amperes 15

Catalog #	Max. DC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series K 3" x 3"					
SD1622-4	90	240	67	2.5000	3/8-16
SD1623-5	112	300	68	2.8750	3/8-16
SD1623-6	135	360	68	3.2500	3/8-16
SD1623-7	157	420	68	3.5000	3/8-16
SD1623-8	180	480	68	3.9375	3/8-16
SD1623-9	202	540	68	4.2500	3/8-16
SD1623-10	225	600	68	4.6250	3/8-16
SD1623-11	247	660	68	5.0000	3/8-16
SD1623-12	270	720	68	5.3125	3/8-16
SD1623-13	292	780	68	5.6875	3/8-16
SD1623-14	315	840	68	6.0000	3/8-16
SD1623-15	337	900	68	6.3750	3/8-16
SD1623-16	360	960	68	6.6875	3/8-16
SD1623-17	382	1020	68	7.0000	3/8-16
SD1623-18	405	1080	68	7.3750	3/8-16
SD1623-19	427	1140	68	7.7500	3/8-16
SD1623-20	450	1200	68	8.0625	3/8-16
SD1623-21	472	1260	68	8.4375	3/8-16
SD1623-22	495	1320	68	8.7500	3/8-16
SD1623-23	517	1380	68	9.1250	3/8-16
SD1623-24	540	1440	68	9.5000	3/8-16
SD1623-25	562	1500	68	9.8750	3/8-16
SD1623-26	585	1560	68	10.1875	3/8-16
SD1623-27	607	1620	68	10.5000	3/8-16
SD1623-28	630	1680	68	10.8750	3/8-16
SD1623-29	652	1720	68	11.2500	3/8-16
SD1623-30	675	1800	68	11.6250	3/8-16

Peak discharge current - amperes 37

Catalog #	Max. DC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series M 4" x 4"					
SD1598-4	90	240	67	2.6875	3/8-16
SD1599-5	112	300	68	3.1875	3/8-16
SD1599-6	135	360	68	3.5625	3/8-16
SD1599-7	157	420	68	4.0000	3/8-16
SD1599-8	180	480	68	4.3750	3/8-16
SD1599-9	202	540	68	4.8125	3/8-16
SD1599-10	225	600	68	5.2500	3/8-16
SD1599-11	247	660	68	5.6250	3/8-16
SD1599-12	270	720	68	6.0625	3/8-16
SD1599-13	292	780	68	6.5000	3/8-16
SD1599-14	315	840	68	6.9375	3/8-16
SD1599-15	337	900	68	7.3750	3/8-16
SD1599-16	360	960	68	7.8125	3/8-16
SD1599-17	382	1020	68	8.2500	3/8-16
SD1599-18	405	1080	68	8.6250	3/8-16
SD1599-19	427	1140	68	9.0625	3/8-16
SD1599-20	450	1200	68	9.4375	3/8-16
SD1599-21	472	1260	68	9.8750	3/8-16
SD1599-22	495	1320	68	10.3125	3/8-16
SD1599-23	517	1380	68	10.6250	3/8-16

Non-Polarized (AC Type)



Catalog #	Max. AC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series K 3" x 3"					
SD2636-1	26	63	67	1.6250	3/8-16
SD2636-2	52	126	68	2.4375	3/8-16
SD2636-3	78	189	68	3.0000	3/8-16
SD2636-4	104	252	68	3.7500	3/8-16
SD2636-5	130	315	68	4.5000	3/8-16
SD2636-6	156	378	68	5.1250	3/8-16
SD2636-7	182	441	68	5.8750	3/8-16
SD2636-8	208	504	68	6.5000	3/8-16
SD2636-9	234	567	68	7.2500	3/8-16
SD2636-10	260	630	68	7.8750	3/8-16
SD2636-11	286	693	68	8.6250	3/8-16
SD2636-12	312	756	68	9.3750	3/8-16
SD2636-13	338	819	68	10.0000	3/8-16
SD2636-14	364	882	68	10.7500	3/8-16
SD2636-15	390	945	68	11.5000	3/8-16
SD2636-16	416	1008	68	12.1250	3/8-16
SD2636-17	442	1071	68	12.8750	3/8-16
SD2636-18	468	1134	68	13.5000	3/8-16
SD2636-19	494	1197	68	14.2500	3/8-16
SD2636-20	520	1260	68	14.8750	3/8-16

Peak discharge current - amperes 37

Catalog #	Max. AC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series M 4" x 4"					
SD2411-1	26	63	67	1.7500	3/8-16
SD2411-2	52	126	67	2.6250	3/8-16
SD2411-3	78	189	68	3.5000	3/8-16
SD2411-4	104	252	68	4.3750	3/8-16
SD2411-5	130	315	68	5.1250	3/8-16
SD2411-6	156	378	68	6.0000	3/8-16
SD2411-7	182	441	68	6.7500	3/8-16
SD2411-8	208	504	68	7.6250	3/8-16
SD2411-9	234	567	68	8.3750	3/8-16
SD2411-10	260	630	68	9.2500	3/8-16
SD2411-11	286	693	68	10.1250	3/8-16
SD2411-12	312	756	68	10.8750	3/8-16
SD2411-13	338	819	68	11.7500	3/8-16
SD2411-14	364	882	68	12.5000	3/8-16
SD2411-15	390	945	68	13.3750	3/8-16
SD2411-16	416	1008	68	14.2500	3/8-16
SD2411-17	442	1071	68	15.0000	3/8-16
SD2411-18	468	1134	68	15.8750	3/8-16
SD2411-19	494	1197	68	16.6250	3/8-16
SD2411-20	520	1260	68	17.5000	3/8-16

Peak discharge current - amperes 70

Catalog #	Max. AC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series S 5" x 6"					
SD2452-1	26	63	68	1.7500	3/8-16
SD2452-2	52	126	68	2.6250	3/8-16
SD2452-3	78	189	68	3.5000	3/8-16
SD2452-4	104	252	68	4.3750	3/8-16
SD2452-5	130	315	68	5.1250	3/8-16
SD2452-6	156	378	68	6.0000	3/8-16
SD2452-7	182	441	68	6.7500	3/8-16
SD2452-8	208	504	68	7.6250	3/8-16
SD2452-9	234	567	68	8.3750	3/8-16
SD2452-10	260	630	68	9.2500	3/8-16
SD2452-11	286	693	68	10.1250	3/8-16
SD2452-12	312	756	68	10.8750	3/8-16
SD2452-13	338	819	68	11.7500	3/8-16
SD-2452-14	364	882	68	12.5000	3/8-16
SD2452-15	390	945	68	13.3750	3/8-16
SD2452-16	416	1008	68	14.2500	3/8-16
SD2452-17	442	1071	68	15.0000	3/8-16
SD2452-18	468	1134	68	15.8750	3/8-16
SD2452-19	494	1197	68	16.6250	3/8-16
SD2452-20	520	1260	68	17.5000	3/8-16

Peak discharge current - amperes 130

Polarized (DC Type)



Catalog #	Max. DC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series M 4" x 4" Continued					
SD1599-24	540	1440	68	11.0000	3/8-16
SD1599-25	562	1500	68	11.4375	3/8-16
SD1599-26	585	1560	68	11.8750	3/8-16
SD1599-27	607	1620	68	12.2500	3/8-16
SD1599-28	630	1680	68	12.6250	3/8-16
SD1599-29	652	1720	68	13.0625	3/8-16
SD1599-30	675	1800	68	13.5000	3/8-16

Peak discharge current - amperes 70

Catalog #	Max. DC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series S 5" x 6"					
SD1772-4	90	240	67	2.8750	3/8-16
SD1772-5	112	300	68	3.2500	3/8-16
SD1772-6	135	360	68	3.6250	3/8-16
SD1772-7	157	420	68	4.1250	3/8-16
SD1772-8	180	480	68	4.5000	3/8-16
SD1772-9	202	540	68	4.8750	3/8-16
SD1772-10	225	600	68	5.3750	3/8-16
SD1772-11	247	660	68	5.7500	3/8-16
SD1772-12	270	720	68	6.1250	3/8-16
SD1772-13	292	780	68	6.6250	3/8-16
SD1772-14	315	840	68	7.0000	3/8-16
SD1772-15	337	900	68	7.3750	3/8-16
SD1772-16	360	960	68	7.7500	3/8-16
SD1772-17	382	1020	68	8.2500	3/8-16
SD1772-18	405	1080	68	8.6250	3/8-16
SD1772-19	427	1140	68	9.0000	3/8-16
SD1772-20	450	1200	68	9.5000	3/8-16
SD1772-21	472	1260	68	9.8750	3/8-16
SD1772-22	495	1320	68	10.2500	3/8-16
SD1772-23	517	1380	68	10.6250	3/8-16
SD1772-24	540	1440	68	11.0000	3/8-16
SD1772-25	562	1500	68	11.5000	3/8-16
SD1772-26	585	1560	68	11.8750	3/8-16
SD1772-27	607	1620	68	12.2500	3/8-16
SD1772-28	630	1680	68	12.7500	3/8-16
SD1772-29	652	1720	68	13.1250	3/8-16
SD1772-30	675	1800	68	13.5000	3/8-16

Peak discharge current - amperes 130

Catalog #	Max. DC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series N 6" x 7 1/4"					
SD2482-4	90	240	67	2.8750	3/8-16
SD2482-5	112	300	68	3.2500	3/8-16
SD2482-6	135	360	68	3.6250	3/8-16
SD2482-7	157	420	68	4.1250	3/8-16
SD2482-8	180	480	68	4.5000	3/8-16
SD2482-9	202	540	68	4.8750	3/8-16
SD2482-10	225	600	68	5.3750	3/8-16
SD2482-11	247	660	68	5.7500	3/8-16
SD2482-12	270	720	68	6.1250	3/8-16
SD2482-13	292	780	68	6.6250	3/8-16
SD2482-14	315	840	68	7.0000	3/8-16
SD2482-15	337	900	68	7.3750	3/8-16
SD2482-16	360	960	68	7.7500	3/8-16
SD2482-17	382	1020	68	8.2500	3/8-16
SD2482-18	405	1080	68	8.6250	3/8-16
SD2482-19	427	1140	68	9.0000	3/8-16
SD2482-20	450	1200	68	9.5000	3/8-16
SD2482-21	472	1260	68	9.8750	3/8-16
SD2482-22	495	1320	68	10.2500	3/8-16
SD2482-23	517	1380	68	10.6250	3/8-16
SD2482-24	540	1440	68	11.0000	3/8-16
SD2482-25	562	1500	68	11.5000	3/8-16
SD2482-26	585	1560	68	11.8750	3/8-16
SD2482-27	607	1620	68	12.2500	3/8-16
SD2482-28	630	1680	68	12.7500	3/8-16
SD2482-29	652	1720	68	13.1250	3/8-16
SD2482-30	675	1800	68	13.5000	3/8-16

Peak discharge current - amperes 200

Non-Polarized (AC Type)



Catalog #	Max. AC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series N 6" x 7 1/4"					
SD2483-1	26	63	67	1.7500	3/8-16
SD2483-2	52	126	67	2.6250	3/8-16
SD2483-3	78	189	68	3.5000	3/8-16
SD2483-4	104	252	68	4.3750	3/8-16
SD2483-5	130	315	68	5.1250	3/8-16
SD2483-6	156	378	68	6.0000	3/8-16
SD2483-7	182	441	68	6.7500	3/8-16
SD2483-8	208	504	68	7.6250	3/8-16
SD2483-9	234	567	68	8.3750	3/8-16
SD2483-10	260	630	68	9.2500	3/8-16
SD2483-11	286	693	68	10.1250	3/8-16
SD2483-12	312	756	68	10.8750	3/8-16
SD2483-13	338	819	68	11.7500	3/8-16
SD2483-14	364	882	68	12.5000	3/8-16
SD2483-15	390	945	68	13.3750	3/8-16
SD2483-16	416	1008	68	14.2500	3/8-16
SD2483-17	442	1071	68	15.0000	3/8-16
SD2483-18	468	1134	68	15.8750	3/8-16
SD2483-19	494	1197	68	16.6250	3/8-16
SD2483-20	520	1260	68	17.5000	3/8-16

Peak discharge current - amperes 200

Catalog #	Max. AC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series V 6" x 10"					
SD2398-1	26	63	69	2.0000	3/8-16
SD2398-2	52	126	69	2.7500	3/8-16
SD2398-3	78	189	69	3.6250	3/8-16
SD2398-4	104	252	69	4.5000	3/8-16
SD2398-5	130	315	69	5.2500	3/8-16
SD2398-6	156	378	69	6.1250	3/8-16
SD2398-7	182	441	69	6.8750	3/8-16
SD2398-8	208	504	69	7.7500	3/8-16
SD2398-9	234	567	69	8.5000	3/8-16
SD2398-10	260	630	69	9.3750	3/8-16
SD2398-11	286	693	69	10.2500	3/8-16
SD2398-12	312	756	69	11.0000	3/8-16
SD2398-13	338	819	69	11.8750	3/8-16
SD2398-14	364	882	69	12.6250	3/8-16
SD2398-15	390	945	69	13.5000	3/8-16
SD2398-16	416	1008	69	14.3750	3/8-16
SD2398-17	442	1071	69	15.1250	3/8-16
SD2398-18	468	1134	69	16.0000	3/8-16
SD2398-19	494	1197	69	16.7500	3/8-16
SD2398-20	520	1260	69	17.6250	3/8-16

Peak discharge current - amperes 270

Catalog #	Max. AC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series X 12" x 16"					
SD4347-4	104	252	70	4.5000	3/8-16
SD4347-5	130	315	70	5.1250	3/8-16
SD4347-6	156	378	70	5.8750	3/8-16
SD4347-7	182	441	70	6.6250	3/8-16
SD4347-8	208	504	70	7.2500	3/8-16
SD4347-9	234	567	70	8.0000	3/8-16
SD4347-10	260	630	70	8.6250	3/8-16
SD4347-11	286	693	70	9.3750	3/8-16
SD4347-12	312	756	70	10.1250	3/8-16
SD4347-13	338	819	70	10.7500	3/8-16
SD4347-14	364	882	70	11.5000	3/8-16
SD4347-15	390	945	70	12.1250	3/8-16
SD4347-16	416	1008	70	12.8750	3/8-16
SD4347-17	442	1071	70	13.5000	3/8-16
SD4347-18	468	1134	70	14.2500	3/8-16
SD4347-19	494	1197	70	15.0000	3/8-16
SD4347-20	520	1260	70	15.6250	3/8-16
SD4347-21	546	1323	70	16.3750	3/8-16
SD4347-22	572	1386	70	17.1250	3/8-16
SD4347-23	598	1449	70	17.7500	3/8-16
SD4347-24	624	1512	70	18.5000	3/8-16
SD4347-25	650	1575	70	19.1250	3/8-16
SD4347-26	676	1638	70	19.8750	3/8-16
SD4347-27	702	1701	70	20.5000	3/8-16
SD4347-28	728	1764	70	21.2500	3/8-16
SD4347-29	754	1827	70	22.0000	3/8-16
SD4347-30	780	1890	70	22.6250	3/8-16
SD4347-31	802	1953	70	23.2500	3/8-16

Peak discharge current - amperes 904

POLARIZED CONTINUED ON NEXT PAGE

Polarized (DC Type)



Catalog #	Max. DC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series V 6" x 10"					
SD2399-4	90	240	69	2.8750	3/8-16
SD2399-5	112	300	69	3.2500	3/8-16
SD2399-6	135	360	69	3.6250	3/8-16
SD2399-7	157	420	69	4.1250	3/8-16
SD2399-8	180	480	69	4.5000	3/8-16
SD2399-9	202	540	69	4.8750	3/8-16
SD2399-10	225	600	69	5.3750	3/8-16
SD2399-11	247	660	69	5.7500	3/8-16
SD2399-12	270	720	69	6.1250	3/8-16
SD2399-13	292	780	69	6.6250	3/8-16
SD2399-14	315	840	69	7.0000	3/8-16
SD2399-15	337	900	69	7.3750	3/8-16
SD2399-16	360	960	69	7.7500	3/8-16
SD2399-17	382	1020	69	8.2500	3/8-16
SD2399-18	405	1080	69	8.6250	3/8-16
SD2399-19	427	1140	69	9.0000	3/8-16
SD2399-20	450	1200	69	9.5000	3/8-16
SD2399-21	472	1260	69	9.8750	3/8-16
SD2399-22	495	1320	69	10.2500	3/8-16
SD2399-23	517	1380	69	10.6250	3/8-16
SD2399-24	540	1440	69	11.0000	3/8-16
SD2399-25	562	1500	69	11.5000	3/8-16
SD2399-26	585	1560	69	11.8750	3/8-16
SD2399-27	607	1620	69	12.2500	3/8-16
SD2399-28	630	1680	69	12.7500	3/8-16
SD2399-29	652	1720	69	13.1250	3/8-16
SD2399-30	675	1800	69	13.5000	3/8-16

Peak discharge current - amperes 270

Catalog #	Max. DC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series X 12" x 16"					
SD4359-4	90	240	70	3.0000	3/8-16
SD4359-5	112	300	70	3.3750	3/8-16
SD4359-6	135	360	70	3.7500	3/8-16
SD4359-7	157	420	70	4.0000	3/8-16
SD4359-8	180	480	70	4.3750	3/8-16
SD4359-9	202	540	70	4.7500	3/8-16
SD4359-10	225	600	70	5.1250	3/8-16
SD4359-11	247	660	70	5.5000	3/8-16
SD4359-12	270	720	70	5.7500	3/8-16
SD4359-13	292	780	70	6.1250	3/8-16
SD4359-14	315	840	70	6.5000	3/8-16
SD4359-15	337	900	70	6.8750	3/8-16
SD4359-16	360	960	70	7.2500	3/8-16
SD4359-17	382	1020	70	7.6250	3/8-16
SD4359-18	405	1080	70	8.0000	3/8-16
SD4359-19	427	1140	70	8.2500	3/8-16
SD4359-20	450	1200	70	8.6250	3/8-16
SD4359-21	472	1260	70	9.0000	3/8-16
SD4359-22	495	1320	70	9.3750	3/8-16
SD4359-23	517	1380	70	9.7500	3/8-16
SD4359-24	540	1440	70	10.0000	3/8-16
SD4359-25	562	1500	69	10.3750	3/8-16
SD4359-26	585	1560	69	10.7500	3/8-16
SD4359-27	607	1620	69	12.0000	3/8-16
SD4359-28	630	1680	69	12.3750	3/8-16
SD4359-29	652	1740	69	12.7500	3/8-16
SD4359-30	675	1800	69	13.8750	3/8-16

Peak discharge current - amperes 904

