

Multiple Devices

Dual Transistors

TYPE	Polarity	Breakdown Voltages (volts)			$h_{FE} @ I_C$ $V_{CE} = 5.0V$		uA	$*h_{FE-1} / h_{FE-2}$ $V_{CE} = 5.0V$		$V_{BE.1} - V_{BE-2}$		$D (V_{BE-1} - V_{BE-2})$ DT DT = -55 to 125°C		ICBO Max nA	Case Style
		VCB	VCE	VEB	Min.	Max.		Min.	Ic (AA)	Max.	Ic (uA)	Max. (uV/°C)	IC (AA)		
2N2060	NPN	100	60	7	30	90	-	0.9	-	5.0	-	10	-	-	TO-77
2N2060A	NPN	100	60	7	30	90	-	0.9	-	3.0	-	10	-	-	TO-77
2N2060B	NPN	100	60	7	30	90	-	-	-	1.5	-	5	-	-	TO-77
2N2223	NPN	100	-	-	25	150	-	-	-	15.0	-	25	-	-	TO-77
2N2223A	NPN	100	-	-	25	150	-	-	-	5.0	-	25	-	-	TO-77
2N2453	NPN	60	30	7	150	600	1000	0.9	1000	3.0	10	10	10	5	TO-78
2N2453A	NPN	80	50	7	150	600	1000	0.9	1000	3.0	10	5	10	5	TO-78
2N2480	NPN	75	40	5	20	-	-	0.8	-	10.0	-	-	-	-	TO-77
2N2480A	NPN	80	40	5	35	-	-	0.8	-	5.0	-	-	-	-	TO-77
2N2639	NPN	45	45	5	50	300	10	0.9	10	5.0	10	10	10	10	TO-78
2N2640	NPN	45	45	5	50	300	10	0.8	10	10.0	10	20	10	10	TO-78
2N2641	NPN	45	45	5	50	300	10	-	-	-	-	-	-	10	TO-78
2N2642	NPN	45	45	5	100	300	10	0.9	10	5.0	10	10	10	10	TO-78
2N2643	NPN	45	45	5	100	300	10	0.8	10	10.0	10	20	10	10	TO-78
2N2644	NPN	45	45	5	100	300	10	-	-	-	-	-	-	10	TO-78
2N2807	PNP	25	20	5	40	120	-100	-	-	-	-	-	-	-10	TO-78
2N2903	NPN	60	30	7	125	625	1000	0.8	1000	10.0	10	20	10	10	TO-78
2N2903A	NPN	60	30	7	125	625	1000	0.9	1000	5	10	10	10	10	TO-78
2N2910	NPN	45	25	-	70	-	100	-	-	-	-	-	-	10	TO-79
2N2913	NPN	45	45	6	60	240	10	-	-	-	-	-	-	10	TO-78
2N2914	NPN	45	45	6	150	600	10	-	-	-	-	-	-	10	TO-78
2N2915	NPN	45	45	6	60	240	10	0.9	100	3	100	10	100	10	TO-78
2N2915A	NPN	45	45	6	100	-	-	-	-	1.5	-	5	-	-	TO-77
2N2916	NPN	45	45	6	150	600	10	0.9	100	3	100	10	100	10	TO-78
2N2916A	NPN	45	45	6	225	-	-	-	-	1.5	-	5	-	-	TO-77
2N2917	NPN	45	45	6	60	240	10	0.8	100	5.0	100	20	100	10	TO-78
2N2918	NPN	45	45	6	150	600	10	0.8	100	5.0	100	20	100	10	TO-78
2N2919	NPN	60	60	6	60	240	10	0.9	100	3.0	100	3.0	100	2	TO-78
2N2919A	NPN	60	60	6	100	-	-	-	-	1.5	-	5	-	-	TO-77
2N2920	NPN	60	60	6	150	600	10	0.9	100	3.0	100	10	100	2	TO-78
2N2920A	NPN	60	60	6	100	-	-	-	-	1.5	-	5	-	-	TO-77
2N2972	NPN	45	45	6	60	240	10	-	-	-	-	-	-	10	TO-71
2N2973	NPN	45	45	6	150	600	10	-	-	-	-	-	-	10	TO-71
2N2974	NPN	45	45	6	60	240	10	0.9	100	3.0	100	10	100	10	TO-71
2N2975	NPN	45	45	6	150	600	10	0.9	100	3.0	100	10	100	10	TO-71
2N2976	NPN	45	45	6	60	240	10	0.8	100	5.0	100	20	100	10	TO-71
2N2977	NPN	45	45	6	150	600	10	0.8	100	5.0	100	20	100	10	TO-71
2N2978	NPN	60	60	6	60	240	10	0.9	100	3.0	100	10	100	2	TO-71
2N2979	NPN	60	60	6	150	600	10	0.9	100	3.0	100	10	100	2	TO-71
2N3423	NPN	30	15	3	20	200	-	0.8	-	10.0	-	40	-	10	TO-79
2N3424	NPN	30	15	3	20	200	-	0.9	-	5.0	-	20	-	10	TO-79
2N3680	NPN	60	50	6	300	-	-	0.9	-	3.0	-	5	-	10	TO-79
2N3907	NPN	60	45	6	60	300	-	0.9	-	1.0	-	5	-	10	TO-79
2N3908	NPN	60	60	6	100	500	-	0.9	-	1.0	-	5	-	2	TO-79